



**SLATE
SOLUTIONS**

SLHIIIA

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ Constructed of 100% Woven Aramid
- ◇ NIJ 0101.06 Threat Level IIIA
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 1.55 psf psf
- ◇ Thickness: .35 in (8.89mm)

Certification Test Results

V50 – 357sig 125gr TMJ (new)	1749 ft/s (533m/s)
V50 – 357sig 125gr TMJ (conditioned)	1781 ft/s (543m/s)
P-BFS Avg. – 357sig 125gr TMJ	26 mm
V50 – 44mag 240gr JHP (new)	1585 ft/s (483m/s)
V50 – 44mag 240gr JHP (conditioned)	1677 ft/s (511m/s)
P-BFS Avg. – 44mag 240gr JHP	33.9 mm

Special Threat Testing

V50 - 2gr RCC	3094 fps (943 m/s)
V50 - 4gr RCC	2746 fps (837 m/s)
V50 - 16gr RCC	2273 fps (693 m/s)
V50 - 17gr FSP (.22cal)	2104 fps (641 m/s)
V50 - 64gr RCC	1900 fps (579 m/s)



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752