



**SLATE  
SOLUTIONS**

**SLRIIIA**

**Soft Armor**



SHOWN IN DELTA CUT

## FEATURES

- ◇ Constructed of 100% Woven Twaron ballistic material
- ◇ NIJ 0101.06 Threat Level IIIA
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 1.55 psf
- ◇ Thickness: .35 in (8.89mm)

## Certification Test Results

V50 – 357sig 125gr TMJ (new)	1822 ft/s (555m/s)
V50 – 357sig 125gr TMJ (conditioned)	1813 ft/s (553m/s)
P-BFS Avg. – 357sig 125gr TMJ	25.5 mm
V50 – 44mag 240gr JHP (new)	1654 ft/s (504m/s)
V50 – 44mag 240gr JHP (conditioned)	1664 ft/s (507m/s)
P-BFS Avg. – 44mag 240gr JHP	34.5 mm

## Special Threat Testing

V50 - 2gr RCC	3129 fps (953m/s)
V50 - 4gr RCC	2723 fps (830m/s)
V50 - 16gr RCC	2261 fps (689m/s)
V50 - 17gr FSP (.22cal)	2133 fps (650m/s)
V50 - 64gr RCC	1919 fps (585m/s)



**SLATE  
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317  
info@SlateSolutions.com | SlateSolutions.com

**754.200.6752**