



**SLATE
SOLUTIONS**

SLSII

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ Constructed of Woven Twaron / UD Twaron and a 70d Nylon Rip Stop w/TPU LAM panel covering
- ◇ NIJ 0101.06 Threat Level II
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 0.85 psf
- ◇ Thickness: .19 in (4.82mm)

Certification Test Results

V50 – 9mm 124gr FMJ	1719 ft/s (523m/s)
P-BFS Avg. – 9mm 124gr FMJ	28.4 mm
V50 – 357mag 158gr JSP	1669 ft/s (509m/s)
P-BFS Avg. – 357mag 158gr JSP	31.4 mm

Special Threat Testing

V50 - 9mm 127gr STX	1575 fps (480m/s)
P-BFS Avg. – 9mm 127gr SXT	35 mm
V50 – 9mm 100gr Frangible	1659 fps (505 m/s)
P-BFS Avg. – 9mm 100gr Frangible	24 mm
V50 - 357sig 125gr GDHP	1660 ft/s (506 m/s)
P-BFS Avg. - 357sig 125gr GDHP	31 mm
V50 – 5.7x28mm 40gr V-Max Blue Tip	2076 fps (633 m/s)
P-BFS Avg. – 5.7x28mm 40gr V-Max Blue Tip	21 mm



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752