



**SLATE
SOLUTIONS**

SLS IIIA

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ Constructed of woven Twaron/UD Twaron ballistic material
- ◇ NIJ 0101.06 Threat Level IIIA
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 1.18 psf
- ◇ Thickness: 0.25" (6.35mm)

Certification Test Results

V50 – 357sig 125gr TMJ (new)	1867 ft/s (569m/s)
V50 – 357sig 125gr TMJ (conditioned)	1796 ft/s (547m/s)
P-BFS Avg. – 357sig 125gr TMJ	27.3 mm
V50 – 44mag 240gr JHP (new)	1661 ft/s (506m/s)
V50 – 44mag 240gr JHP (conditioned)	1613 ft/s (492m/s)
P-BFS Avg. – 44mag 240gr JHP	36 mm

Special Threat Testing

V50 - 2gr RCC	3060 ft/s (932m/s)
V50 - 4gr RCC	2642 ft/s (805m/s)
V50 - 16gr RCC	2244 ft/s (684m/s)
V50 - 17gr FSP (.22cal)	2017 ft/s (615m/s)
V50 - 64gr RCC	1866 ft/s (569m/s)
V50 – 9mm 127gr SXT (new)	1754 ft/s (534m/s)
P-BFS Avg. – 9mm 127gr SXT	24.6 mm
P-BFS Avg. – 40cal 165gr S+W Sp GDHP	27.2 mm
P-BFS Avg. – 5.7x28 27gr SS195	17 mm
P-BFS Avg. – 5.7x28 27gr SS197	19.3 mm



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752