



**SLATE
SOLUTIONS**

SLXII

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ Constructed of Woven Twaron/ Spectra Shield II and a 70D Nylon Rip Stop with TPU LAM panel covering
- ◇ NIJ 0101.06 Threat Level II
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 0.69 psf
- ◇ Thickness: 0.19" (4.82mm)

Certification Test Results

| | |
|-------------------------------|--------------------|
| V50 – 9mm 124gr FMJ | 1654 ft/s (504m/s) |
| P-BFS Avg. – 9mm 124gr FMJ | 30.8 mm |
| V50 – 357mag 158gr JSP | 1626 ft/s (496m/s) |
| P-BFS Avg. – 357mag 158gr JSP | 30.9 mm |

Special Threat Testing

| | |
|------------------------------------|---------------------|
| V50 - 2gr RCC | 2645 fps (806 m/s) |
| V50 - 4gr RCC | 2315 fps (706 m/s) |
| V50 - 16gr RCC | 1937 fps (590 m/s) |
| V50 - 17gr FSP (.22cal) | 1836 fps (560 m/s) |
| V50 - 64gr RCC | 1790 fps (546 m/s) |
| V50 - 9mm 124gr GDHP | 1686 ft/s (514 m/s) |
| P-BFS Avg. - 9mm 124gr GDHP | 27.9 mm |
| V50 – 9mm 127gr SXT | 1586 fps (483 m/s) |
| P-BFS Avg. – 9mm 127gr SXT | 29 mm |
| V50 – 40cal 165gr GDHP | NA* |
| P-BFS Avg. – 40cal 165gr GDHP | 29 mm |
| V50 – 5.7x28mm 40gr SS197 Blue Tip | 2071 fps (631 m/s) |

*Testing Terminated Due to Velocity Limitation



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752