



**SLATE
SOLUTIONS**

SLS IIIA FEMALE

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ◇ Constructed of woven Twaron/UD Twaron/Dyneema ballistic material
- ◇ NIJ 0101.06 Threat Level IIIA, Model 3/18F
- ◇ NIJ Certification Sizes C1 – C5
- ◇ Weight: 1.05 psf
- ◇ Thickness: 0.21" (4.06mm)

Certification Test Results

V50 - 357sig 125gr FMJ (new)	1895 ft/s (577 m/s) / 1867 ft/s (569 m/s)
V50 - 357sig 125gr FMJ (conditioned)	1788 ft/s (545 m/s) / 1796 ft/s (547 m/s)
P-BFS Avg. - 357sig 125gr FMJ	24.9 mm / 27.3 mm
V50 - 44mag 240gr SJHP (new)	1740 ft/s (530 m/s) / 1661 ft/s (506 m/s)
V50 - 44mag 240gr SJHP (conditioned)	1694 ft/s (516 m/s) / 1613 ft/s (492 m/s)
P-BFS Avg. - 44mag 240gr SJHP	35.6 mm / 36 mm



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317
info@SlateSolutions.com | SlateSolutions.com

754.200.6752