



**SLATE  
SOLUTIONS**

**SLSIIIA**

**Soft Armor**



SHOWN IN DELTA CUT

## FEATURES

- ♦ The SLS ballistic package stands out as one of our top-performing yet cost-effective options. It's an ideal selection for officers seeking the optimal balance of comfort, value, and flexibility within a 100% aramid hybrid design.
- ♦ Covered with a 70d Nylon Rip Stop with TPU backing, heat sealed material.

## Specifications

|                       |                 |
|-----------------------|-----------------|
| Threat Level (NIJ 06) | IIIA            |
| Certification Sizes   | C1 - C5         |
| Weight (AD)           | 1.18 psf        |
| Thickness (in)        | 0.27" (6.86 mm) |

## Certification Test Results

|                                      |                     |
|--------------------------------------|---------------------|
| V50 - 357sig 125gr FMJ (new)         | 1867 ft/s (569 m/s) |
| V50 - 357sig 125gr FMJ (conditioned) | 1796 ft/s (547 m/s) |
| P-BFS Avg. - 357sig 125gr FMJ        | 27.3 mm             |
| V50 - 44mag 240gr SJHP (new)         | 1661 ft/s (506 m/s) |
| V50 - 44mag 240gr SJHP (conditioned) | 1613 ft/s (492 m/s) |
| P-BFS Avg. - 44mag 240gr SJHP        | 36 mm               |

## Special Threat Testing

|                                      |                    |
|--------------------------------------|--------------------|
| V50 - 2gr RCC                        | 3060 ft/s (932m/s) |
| V50 - 4gr RCC                        | 2642 ft/s (805m/s) |
| V50 - 16gr RCC                       | 2244 ft/s (684m/s) |
| V50 - 17gr FSP (.22cal)              | 2017 ft/s (615m/s) |
| V50 - 64gr RCC                       | 1866 ft/s (569m/s) |
| V50 - 9mm 127gr SXT (new)            | 1754 ft/s (534m/s) |
| P-BFS Avg. - 9mm 127gr SXT           | 24.6 mm            |
| P-BFS Avg. - 40cal 165gr S+W Sp GDHP | 27.2 mm            |
| P-BFS Avg. - 5.7x28 27gr SS195       | 17 mm              |
| P-BFS Avg. - 5.7x28 27gr SS197       | 19.3 mm            |



**SLATE  
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317 USA  
info@SlateSolutions.com | SlateSolutions.com

**+1.754.200.6752**