



**SLATE
SOLUTIONS**

SLSII

Soft Armor



SHOWN IN DELTA CUT

FEATURES

- ♦ The SLS ballistic package stands out as one of our top-performing yet cost-effective options. It's an ideal selection for officers seeking the optimal balance of comfort, value, and flexibility within a 100% aramid hybrid design.
- ♦ Covered with a 70D nylon Rip Stop with TPU backing, heat sealed material.

Specifications

Threat Level (NIJ 06)	II
Certification Sizes	C1 - C5
Weight (AD)	0.85 psf
Thickness (in)	0.19" (4.82mm)

Certification Test Results

V50 - 9mm 124gr FMJ (new)	1719 ft/s (523 m/s)
V50 - 9mm 124gr FMJ (conditioned)	1605 ft/s (489 m/s)
P-BFS Avg. - 9mm 124gr FMJ	28.4 mm
V50 - 357mag 158gr JSP (new)	1669 ft/s (509 m/s)
V50 - 357mag 158gr JSP (conditioned)	1574 ft/s (479 m/s)
P-BFS Avg. - 357mag 158gr JSP	31.4 mm

Special Threat Testing

V50 - 9mm 127gr STX	1575 fps (480m/s)
P-BFS Avg. - 9mm 127gr SXT	35 mm
V50 - 9mm 100gr Frangible	1659 fps (505 m/s)
P-BFS Avg. - 9mm 100gr Frangible	24 mm
V50 - 357sig 125gr GDHP	1660 ft/s (506 m/s)
P-BFS Avg. - 357sig 125gr GDHP	31 mm
V50 - 5.7x28mm 40gr V-Max Blue Tip	2076 fps (633 m/s)
P-BFS Avg. - 5.7x28mm 40gr V-Max Blue Tip	21 mm



**SLATE
SOLUTIONS**

7060 W. State Road 84, Suite 12, Davie, FL 33317 USA
info@SlateSolutions.com | SlateSolutions.com

+1.754.200.6752